



**MATERIAL
SAFETY
DATA SHEET**
Revised 29TH June 2017

PROFESSIONAL PAINT STRIPPER

SECTION 1 : IDENTIFICATION OF SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name: PROFESSIONAL PAINT STRIPPER
Product code: 0575

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance/mixture: Paint and varnish remover. Restricted to industrial use and to professionals approved in certain EU member states-verify where use is allowed.

1.3 Details of the supplier of the safety data sheet

Company name: R. K. & J. Jones Ltd
Southery Road
Feltwell
Thetford
Norfolk
IP26 4EH

Telephone: 01842 828101
Email: sales@birdbrand.co.uk

1.4 Emergency telephone number

Emergency number: 01223 968282

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification under CLP: STOT SE 2: H371; STOT SE 3: H335; STOT SE 3: H336; Acute Tox. 4: H302+312+332; Carc.2: H351; Eye Irrit.2: H319; STOT RE 2: H373; Skin Irrit.2: H315

Most important adverse Effects:

Harmful if swallowed, in contact with skin or if inhaled. May cause damage to organs liver/blood through prolonged or repeated exposure. Causes serious eye irritation. Suspected of causing cancer. May cause respiratory irritation. May cause drowsiness or dizziness.

2.2 Label elements

Label elements:

Hazard statements: H302+312+332: Harmful if swallowed, in contact with skin or if inhaled.
H371: May cause damage to organs liver/blood through prolonged or repeated exposure.
H319: Causes serious eye irritation.
H351: Suspected of causing cancer
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.

Hazard pictograms:

GHS07: Exclamation mark
GHS08: Health hazard



Signal words:

Precautionary statements:

Warning

- P102: Keep out of reach of children.
- P202: Do not handle until all safety precautions have been read and understood.
- P233: Keep container tightly closed.
- P260: Do not breathe fumes/vapours.
- P262: Do not get in eyes, on skin, or on clothing.
- P271: Use only outdoors or in a well-ventilated area.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P301+310: IF SWALLOWED: Immediately call a POISON CENTER/Doctor.
- P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
- P315: Get immediate medical advice/attention.
- P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE/doctor.
- P405: Store locked up
- P501: Dispose of contents/container to a licensed waste contractor.

2.3 Other hazards

Other hazards:

Danger of serious damage to health by prolonged exposure.

PBT:

This product is not identified as a PBT/vPvB substance.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous ingredients:

DICHLOROMETHANE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-838-9	75-09-2	-	Carc. 2: H351	>45%

METHANOL

200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	2.9-9.9%
-----------	---------	---	---	----------

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Skin contact

Remove affected person from source of contamination. Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Get medical attention promptly if symptoms occur after washing.

- Eye contact:** Promptly wash eyes with plenty of water while lifting the eyelids. Continue to rinse for at least 15 minutes and get medical attention.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Obtain immediate medical attention.

4.2 Most important symptoms and effects, both acute and delayed

- Skin contact** There may be mild irritation at the site of contact.
- Eye contact:** There may be irritation and redness.
- Ingestion:** There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.
- Inhalation:** Absorption through lungs can occur causing symptoms similar to those of ingestion.
- Delayed/immediate effects:** Immediate effects can be expected after short-term exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Immediate/special treatment: Show this safety data sheet to the doctor in attendance.

SECTION 5: FIRE FIGHTING MEASURES

5.1 Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2 Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes

5.3 Advice for fire fighters:

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2 Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3 Clean-up procedures

Clean up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4 Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.
Suitable packaging: Must only be kept in original packaging.

7.3 Specific end use(s)

Specific end use(s): No data available

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Hazardous ingredients:
DICHLOROMETHANE

Workplace exposure limits: **Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	350 mg/m ³	1060 mg/m ³	-	-

METHANOL

UK	266 mg/m ³	333 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

DNEL/PNEC Values

Hazardous ingredients:
METHANOL

Type	Exposure	Value	Population	Effect
DNEL	Dermal - long term	40mg/kg/day	Workers	-
DNEL	Inhalation - Long term	260mg/m ³	Workers	-
DNEL	Dermal - Short term	40mg/kg/day	Workers	-
DNEL	Inhalation - Short term	260 mg/m ³	Workers	-
DNEL	Dermal - Long term	8 mg/kg/day	Consumers	-
DNEL	Inhalation - Long term	50 mg/m ³	Consumers	-
DNEL	Dermal - Short term	8 mg/kg/day	Consumers	-
DNEL	Dermal - Short term	50 mg/m ³	Consumers	-
DNEL	Oral - Short term	8 mg/kg/day	Consumers	-

8.2 Exposure controls

Engineering measures: Effective ventilation in processing areas, and for the drying of stripped

articles: local exhaust ventilation at strip tanks supplemented by forced ventilation in those areas, to minimise exposure and to ensure compliance with relevant exposure limits. All handling to take place in well-ventilated area. Explosion-proof general and local exhaust ventilation.

Respiratory protection:	Wear suitable respiratory protective equipment if exposure to levels above the occupational exposure limit is likely. Positive air supplied RPE is recommended.
Hand protection:	Protective gloves
Eye protection:	Ensure eye bath is to hand. Wear eye/face protection. Wear approved chemical safety goggles at all times. Ensuring they are tightly fitted.
Skin protection:	Wear suitable protective clothing and gloves. Gloves should be changed when permeation is likely. PVC has a breakthrough time of approximately 5 minutes for methylene chloride.
Environmental:	An environmental assessment must be made to ensure compliance with local environmental legislation.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties

State:	Liquid
Colour:	Off-white
Odour:	Strong DCM odour
Evaporation rate:	Moderate
Solubility in water:	Slightly soluble
Viscosity:	Viscous
Boiling point range °C:	>35
Flash point °C:	60-93
Relative density:	1.25 +/-0.5
Part. Coeff. N-octanol/water:	No data available
Vapour Pressure:	355 at 20 Deg C.
pH:	Approx. 7
VOC g/l:	970

9.2 Other information

Other information:	No data available
---------------------------	-------------------

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity	Stable under recommended transport or storage conditions.
-------------------	---

10.2 Chemical stability

Chemical stability	Stable under normal conditions.
---------------------------	---------------------------------

10.3 Possibility of hazardous reactions

Hazardous reactions	Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.
----------------------------	---

10.4 Conditions to avoid

Conditions to avoid	Heat
----------------------------	------

10.5 Incompatible materials

Materials to avoid	Strong oxidising agents. Strong acids.
---------------------------	--

10.6 Hazardous decomposition products

Haz. Decomp. products In combustion emits toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

Hazardous ingredients:

DICHLOROMETHANE

ORL	MUS	LD50	4770	mg/kg
ORL	RAT	LD50	5350	mg/kg
SCU	MUS	LD50	6460	mg/kg

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg

ORL	RAT	LD50	5628	mg/kg
-----	-----	------	------	-------

Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH DRM ING	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Carcinogenicity	--	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

Symptom/routes of exposure

Skin contact: There may be mild irritation at the site of contact.
Eye contact There may be irritation and redness
Ingestion There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.
Inhalation Absorption through the lungs can occur causing symptoms similar to those of ingestion.
Delayed/immediate effects Immediate effects can be expected after short-term exposure.
Other information CARCINOGENICITY: Chronic inhalation studies in mice have shown increases in lung and liver tumours, when exposed to concentrations of Methylene chloride well in excess of the occupational exposure limit.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Ecotoxicity values

SECTION 15: REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Specific regulations**

Restricted to industrial use and to professionals approved in certain EU Member states-verify where use is allowed. EU decision number 4551009/ EC 6th May 2009. EU Legislation: DECISION No455/2009/EC of The European Parliament and of the Council of 6 May 2009 Amendment to Annex 1 to Directive 76/769/EEC – Applicable to sales Within the European Union. Industrial users require the following Provisions: (a) to (e) below (a) effective ventilation in all processing Areas, in particular for the wet processing and the drying of stripped Articles: local exhaust ventilation at strip tanks supplemented by Forced ventilation in those areas, so as to minimise exposure and to ensure compliance, where technically feasible, with relevant occupational exposure limits; (b) measures to minimise evaporation from strip tanks comprising: lids for covering strip tanks except during loading and unloading; suitable loading and unloading arrangements for strip tanks; and wash tanks with water or brine to remove excess solvent after unloading (c) measures for the safe handling of dichloromethane in strip tanks comprising: pumps and pipework for transferring paint stripper to and from strip tanks; and suitable arrangements for safe cleaning of tanks and removal of sludge; (d) personal protective equipment that complies with Directive 89/686/EEC comprising: suitable protective gloves, safety goggles and protective clothing; and appropriate respiratory protective equipment where compliance with relevant occupational exposure limits cannot be otherwise achieved;(e) adequate information, instruction and training for operators in the use of such equipment. National regulations: Users of this product are reminded of their duties under the current Control of Substances Hazardous to Health Regulations and a suitable and sufficient Assessment of all the risk should be undertaken before using this product.

15.2 Chemical Safety Assessment

Chemical safety assessment A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

SECTION 16: OTHER HEALTH AND SAFETY INFORMATION**Other information**

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830 *indicates text in the SDS which has changed since the last revision.

Phrases used in S2 and S3

H225: Highly flammable liquid and vapour
 H301: Toxic if swallowed
 H302+312+332: Harmful if swallowed, in contact with skin or if inhaled.
 H311: Toxic in contact with skin.
 H319: Causes serious eye irritation.
 H331: Toxic if inhaled.
 H335: May cause respiratory irritation
 H336: May cause drowsiness or dizziness.
 H351: Suspected of causing cancer.
 H370 Causes damage to organs.
 H371: May cause damage to organs.

Material Safety Data Sheet

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own use. If this product is re-distributed and re-formulated for sale, details of its hazards and recommended methods for safe handling must be passed to customers. Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by a work activity using this product is undertaken before this product is used.

Note: The information contained in this Safety Data Sheet does not constitute the users own assessment of workplace risk as required by other Health & Safety Legislation (e.g. the Health and Safety at Work Act,1974; the control of Substances Hazardous to Health Regulations,1988). The data given here is based on current knowledge and experience. The purpose of this data sheet is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the product's properties.